

## **Galaxis 88 STB**



## **Product Description**

State of the art HD satellite receiver with cutting edge technology featuring PVR ready via integrated USB interface designed to offer the viewer a versatile experience. Advanced security chipset pairing with embedded Conax CAS7 Conditional Access System. High distinctive features include: user-friendly HD graphic interface and 7 MBC HD Channels.

### **Product Features**

### **Distinctive Characteristics**

- DVB-S2
- 7 day EPG Grid Format
- Smart Card Reader
- USB PVR Ready
- Multi Language OSD: Arabic, English, French, Farsi, Tagalog & Urdu
- Parental Access Control
- 5000 TV & Radio Channels
- Favourite Settings
- Conax CAS 7 Advanced Security

#### Main components

- 8 MB Flash Memory
- 128 MB SDRAM

## **Output Connection**

- 1 \* RCA (CVBS)
- 2 \* RCA Audio (R/L)
- S/PDIF (Electrical/Optical)
- •1 \* HDMI 1.2/HDCP
- •1\*YPbPr

#### Accessories

- Owner Manual
- Remote Control Unit (Inc. batteries)
- HDMI Cable

#### Power

• External Power supply

### **Technical specifications**

#### Tuner & Channel


Number of Tuners Input Connector Frequency Range Symbol Rate

Demodulation

#### MPEG Transport Stream A/V Decoding

Profile Level Video Format Video System Video Resolution Audio Mode Sampling Rate Single DVB-S2 incl. Loop Through (13/18V, 500mA max.) F-type 950-2150MHz DVB-S: 2-45Ms/s, DVB-S2:10-30Ms/s (QPSK), 10-31Ms/s (8PSK) QPSK, 8PSK QPSK: 1/4,1/3,2/5,1/2,3/5,2/3,3/4,4/5,5/6,8/9,9/10 8PSK: 3/5,2/3,3/4,5/6,8/9,9/10 16APSK: 2/3,3/4,4/5,5/6,8/9,9/10

MPEG-2 MP@ML, MPEG-2 MP@HL, MPEG-4 AVC/H.264 HP@L4 4:3/16:9 PAL / NTSC 1080p,1080i,720p,576p Single Channel, Dual Channel, Joint Stereo, Stereo 32, 44.1 & 48KHz



 $\sum$  conax



**Best In HD TV Entertainment** 

# **Galaxis 88 STB**



**Technical specifications** 

Memory Flash Memory SDRAM

Input / Output (Optional) DiSEqC Video Audio Digital audio output USB 2.0

Display Front Panel

Front Panel Buttons

Power Supply Input Voltage

Update Of Software

Accessories

**Security Features** 

8MB 128MB

DiSEqC 1.2, Auto DiSEqC RCA Video (CVBS), HDMI 1.2, YPbPr RCA Audio (L/R) Electrical/Optical SPDIF PVR and Time shift

Status LED 7 Segment LED Display (blue)

7 buttons front panel

External Power Supply / 12VDC / 1.5A

Support for over the air update (OTA)

IR remote control, incl. batteries Owner Manual, HDMI Cable

Conax advanced security Chipset pairing with Conditional access Smart Card



For orders, pricing, availability, technical assistance or other inquiries please contact:

My-HD Media Boutique Villa 6 Knowledge Village, Dubai Tel: +971 4 435 4800 Fax: +971 4 435 4889 sales@my-hd.tv www.my-hd.tv

